



<b>Product Code: 951-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.3</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX CEILING FLAT</b>
<b>Product Code</b>	951-100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Use as a decorative coating on ceilings and low traffic areas. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

Classified as **Non-Hazardous, Non-Dangerous Goods** according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.

**Poisons Schedule** None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
	Water	7732-18-5	40-50%
	Pigments		30-40%
	Synthetic Polymers		10-20%
	Other ingredients determined not to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed immediately contact Doctor or Poisons Information Centre
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. . Seek fresh air and keep at rest until fully recovered. Seek medical attention is effects persist.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	No specific hazards
<b>Extinguishing Media</b>	Not combustible. Use water, foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational Exposure Limits</b>	No exposure limits set by Safe Work Australia
<b>Engineering Control Measures</b>	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
<b>Personal Protection</b>	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous Liquid	<b>Solubility in water</b>	Miscible with water
<b>Odour</b>	Mild	<b>pH as supplied</b>	8-10
<b>Colour</b>	White or tinted colour	<b>Vapour pressure (20°C)</b>	Not Available
<b>Boiling Point</b>	Approx. 100°C	<b>Evaporation rate</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Auto-ignition Temp (C)</b>	Not Available
<b>Specific Gravity</b>	1.3 – 1.5 at 25°C	<b>Volatile (% Wt.)</b>	40-50
<b>Flash Point</b>	Not Available	<b>Decomposition Temp(C)</b>	Not Available
<b>Flammability Limits</b>	Not Available		

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Product is considerable stable and hazardous polymerisation will not occur.
------------------	---

## 11. TOXICOLOGICAL INFORMATION

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting

**12. ECOLOGICAL INFORMATION**

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION**

<b>Road and Rail Transport</b>	<b>Marine Transport</b>	<b>Air Transport</b>
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as Non-Hazardous, Non-Dangerous Goods according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.
<b>Poisons Schedule</b>	None allocated
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	None allocated
<b>Safety Phrase(s)</b>	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S46: If swallowed immediately contact Doctor or Poisons Information Centre.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints (Aust) Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 952-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.3</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX ACRYLIC SEALER UNDERCOAT</b>
<b>Product Code</b>	952-100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Suitable for masonry, plaster, plasterboard, fibro, paper-faced wallboards and appropriately primed metal. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

Classified as **Non-Hazardous, Non-Dangerous Goods** according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.

**Poisons Schedule** None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
Water		7732-18-5	30-40%
Pigments			30-40%
Synthetic Polymers			10-20%
Other ingredients determined not to be hazardous			to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed immediately contact Doctor or Poisons Information Centre
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. . Seek fresh air and keep at rest until fully recovered. Seek medical attention is effects persist.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	No specific hazards
<b>Extinguishing Media</b>	Not combustible. Use water, foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Fire fighters and others exposed to vapours or products of combustion should wear

self-contained breathing apparatus and suitable protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational Exposure Limits</b>	No exposure limits set by Safe Work Australia
<b>Engineering Control Measures</b>	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
<b>Personal Protection</b>	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous Liquid	<b>Solubility in water</b>	Miscible with water
<b>Odour</b>	Mild	<b>pH as supplied</b>	8-10
<b>Colour</b>	White or tinted colour	<b>Vapour pressure (20°C)</b>	Not Available
<b>Boiling Point</b>	Approx. 100°C	<b>Evaporation rate</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Auto-ignition Temp (C)</b>	Not Available
<b>Specific Gravity</b>	1.3 – 1.4 at 25°C	<b>Volatile (% Wt.)</b>	40-50
<b>Flash Point</b>	Not Available	<b>Decomposition Temp(C)</b>	Not Available
<b>Flammability Limits</b>	Not Available		

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Product is considerable stable and hazardous polymerisation will not occur.
------------------	---

## 11. TOXICOLOGICAL INFORMATION

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

## 13. DISPOSAL CONSIDERATIONS

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

## 14. TRANSPORT INFORMATION

Road and Rail Transport	Marine Transport	Air Transport
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

## 15. REGULATORY INFORMATION

<b>Classification</b>	Classified as Non-Hazardous, Non-Dangerous Goods according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.
<b>Poisons Schedule</b>	None allocated
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	None allocated
<b>Safety Phrase(s)</b>	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S46: If swallowed immediately contact Doctor or Poisons Information Centre.

## 16. OTHER INFORMATION

This safety data sheet prepared by Colourtrend Paints Australia Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 953-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX LOW SHEEN ACRYLIC</b>
<b>Product Code</b>	953-100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Suitable for interior and exterior walls and ceilings. Not recommended for timber. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

Classified as **Non-Hazardous, Non-Dangerous Goods** according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.

**Poisons Schedule** None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Chemical Characterisation** Liquid

<u>Ingredients</u>	<u>Name</u>	<u>CAS Number</u>	<u>Proportion</u>
Water		7732-18-5	20-30%
Pigments			20-30%
Synthetic Polymers			30-40%
Other ingredients determined not to be hazardous			to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed immediately contact Doctor or Poisons Information Centre
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. . Seek fresh air and keep at rest until fully recovered. Seek medical attention is effects persist.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	No specific hazards
<b>Extinguishing Media</b>	Not combustible. Use water, foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational Exposure Limits</b>	No exposure limits set by NOHSC
<b>Engineering Control Measures</b>	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
<b>Personal Protection</b>	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous Liquid	<b>Solubility in water</b>	Miscible with water
<b>Odour</b>	Mild	<b>pH as supplied</b>	8-10
<b>Colour</b>	White or tinted colour	<b>Vapour pressure (20<sup>0</sup>C)</b>	Not Available
<b>Boiling Point</b>	Approx. 100 <sup>0</sup> C	<b>Evaporation rate</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Auto-ignition Temp (C)</b>	Not Available
<b>Specific Gravity</b>	1.2 – 1.3 at 25 <sup>0</sup> C	<b>Volatile (% Wt.)</b>	40-50
<b>Flash Point</b>	Not Available	<b>Decomposition Temp(C)</b>	Not Available
<b>Flammability Limits</b>	Not Available		

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Product is considerable stable and hazardous polymerisation will not occur.
------------------	---

## 11. TOXICOLOGICAL INFORMATION

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting



**12. ECOLOGICAL INFORMATION**

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION**

**Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

**Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

**Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as Non-Hazardous, Non-Dangerous Goods according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.
<b>Poisons Schedule</b>	None allocated
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	None allocated
<b>Safety Phrase(s)</b>	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S46: If swallowed immediately contact Doctor or Poisons Information Centre.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints Australia Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 954-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX SATIN ACRYLIC</b>
<b>Product Code</b>	954-100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Suitable for interior and exterior walls and ceilings. Not recommended for timber. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

Classified as **Non-Hazardous, Non-Dangerous Goods** according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.

**Poisons Schedule** None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
	Water	7732-18-5	20-30%
	Pigments		20-30%
	Synthetic Polymers		40-50%
	Other ingredients determined not to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed immediately contact Doctor or Poisons Information Centre
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Seek fresh air and keep at rest until fully recovered. Seek medical attention if effects persist.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	No specific hazards
<b>Extinguishing Media</b>	Not combustible. Use water, foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Occupational Exposure Limits</b>	No exposure limits set by NOHSC
<b>Engineering Control Measures</b>	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
<b>Personal Protection</b>	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Viscous Liquid	<b>Solubility in water</b>	Miscible with water
<b>Odour</b>	Mild	<b>pH as supplied</b>	8-10
<b>Colour</b>	White or tinted colour	<b>Vapour pressure (20°C)</b>	Not Available
<b>Boiling Point</b>	Approx. 100°C	<b>Evaporation rate</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Auto-ignition Temp (C)</b>	Not Available
<b>Specific Gravity</b>	1.2 – 1.3 at 25°C	<b>Volatile (% Wt.)</b>	40-50
<b>Flash Point</b>	Not Available	<b>Decomposition Temp(C)</b>	Not Available
<b>Flammability Limits</b>	Not Available		

**10. STABILITY AND REACTIVITY**

<b>Stability</b>	Product is considerable stable and hazardous polymerisation will not occur.
------------------	---

**11. TOXICOLOGICAL INFORMATION**

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting

**12. ECOLOGICAL INFORMATION**

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION**

<b>Road and Rail Transport</b>	<b>Marine Transport</b>	<b>Air Transport</b>
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as Non-Hazardous, Non-Dangerous Goods according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.
<b>Poisons Schedule</b>	None allocated
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	None allocated
<b>Safety Phrase(s)</b>	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S46: If swallowed immediately contact Doctor or Poisons Information Centre.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints Australia Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 955-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX MATT ACRYLIC</b>
<b>Product Code</b>	955-100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Suitable for interior and exterior walls and ceilings. Not recommended for timber. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

Classified as **Non-Hazardous, Non-Dangerous Goods** according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.

**Poisons Schedule** None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
	Water	7732-18-5	20-30%
	Pigments		30-40%
	Synthetic Polymers		30-40%
	Other ingredients determined not to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed immediately contact Doctor or Poisons Information Centre
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Seek fresh air and keep at rest until fully recovered. Seek medical attention if effects persist.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	No specific hazards
<b>Extinguishing Media</b>	Not combustible. Use water, foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Occupational Exposure Limits</b>	No exposure limits set by Safe Work Australia
<b>Engineering Control Measures</b>	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
<b>Personal Protection</b>	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Viscous Liquid	<b>Solubility in water</b>	Miscible with water
<b>Odour</b>	Mild	<b>pH as supplied</b>	8-10
<b>Colour</b>	White or tinted colour	<b>Vapour pressure (20°C)</b>	Not Available
<b>Boiling Point</b>	Approx. 100°C	<b>Evaporation rate</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Auto-ignition Temp (C)</b>	Not Available
<b>Specific Gravity</b>	1.3 – 1.4 at 25°C	<b>Volatile (% Wt.)</b>	40-50
<b>Flash Point</b>	Not Available	<b>Decomposition Temp(C)</b>	Not Available
<b>Flammability Limits</b>	Not Available		

**10. STABILITY AND REACTIVITY**

<b>Stability</b>	Product is considerable stable and hazardous polymerisation will not occur.
------------------	---

**11. TOXICOLOGICAL INFORMATION**

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

## 13. DISPOSAL CONSIDERATIONS

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

## 14. TRANSPORT INFORMATION

Road and Rail Transport	Marine Transport	Air Transport
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

## 15. REGULATORY INFORMATION

<b>Classification</b>	Classified as Non-Hazardous, Non-Dangerous Goods according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.
<b>Poisons Schedule</b>	None allocated
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	None allocated
<b>Safety Phrase(s)</b>	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S46: If swallowed immediately contact Doctor or Poisons Information Centre.

## 16. OTHER INFORMATION

This safety data sheet prepared by Colourtrend Paints Australia Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 956-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX BLOCK FILLER</b>
<b>Product Code</b>	956-100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Use as a filler coating on masonry structures. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

Classified as **Non-Hazardous, Non-Dangerous Goods** according to criteria of Safe Work Australia and the Australian Dangerous Goods Code for transport by Road & Rail.

**Poisons Schedule** None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	<b>Liquid</b>		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
Water		7732-18-5	20-30%
Pigments			30-60%
Synthetic Polymers			10-20%
Other ingredients determined not to be hazardous			to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed immediately contact Doctor or Poisons Information Centre
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Seek fresh air and keep at rest until fully recovered. Seek medical attention if effects persist.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	No specific hazards
<b>Extinguishing Media</b>	Not combustible. Use water, foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Fire fighters and others exposed to vapours or products of combustion should wear



self-contained breathing apparatus and suitable protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational Exposure Limits</b>	No exposure limits set by Safe Work Australia
<b>Engineering Control Measures</b>	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
<b>Personal Protection</b>	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous Liquid	<b>Solubility in water</b>	Miscible with water
<b>Odour</b>	Mild	<b>pH as supplied</b>	8-10
<b>Colour</b>	White or tinted colour	<b>Vapour pressure (20°C)</b>	Not Available
<b>Boiling Point</b>	Approx. 100°C	<b>Evaporation rate</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Auto-ignition Temp (C)</b>	Not Available
<b>Specific Gravity</b>	1.5 – 1.7 at 25°C	<b>Volatile (% Wt.)</b>	30-40
<b>Flash Point</b>	Not Available	<b>Decomposition Temp(C)</b>	Not Available
<b>Flammability Limits</b>	Not Available		

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Product is considerable stable and hazardous polymerisation will not occur.
------------------	---

## 11. TOXICOLOGICAL INFORMATION

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.

**COLOURTREND PAINTS AUSTRALIA PTY LTD - SDS**

Product Code: 956-100

Issue Date: 5/06/2013

Issue No.1

**Swallowed**

Swallow may result in nausea, abdominal irritation and vomiting

**12. ECOLOGICAL INFORMATION**

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION****Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

**Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

**Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as Non-Hazardous, Non-Dangerous Goods according to criteria of Safe Work Australia & the Australian Dangerous Goods Code for transport by Road & Rail.
<b>Poisons Schedule</b>	None allocated
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	None allocated
<b>Safety Phrase(s)</b>	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S46: If swallowed immediately contact Doctor or Poisons Information Centre.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints Australia Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 957-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.1</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	COVERMAX GLOSS ENAMEL
<b>Product Code</b>	957 -100
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Use as a decorative & protective coating on timber structures. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

This material is **Hazardous** according to criteria of Safe Work Australia. Classified as **Dangerous Goods** by the criteria of the Australian Dangerous Goods Code for transport by Road & Rail.

<b>Risk Phrases</b>	Xi: Flammable. Irritating to skin
<b>Safety Phrases</b>	Keep out of reach of children, do not breathe vapour, and avoid contact with skin and eyes. If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Poisons Schedule</b>	None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
	Kerosene	8008-20-6	10-15%
	Mineral Turps		<5%
	Synthetic Polymer		50-60%
	Pigments		20-30%
	Other ingredients determined not to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Apply air resuscitation if breathing is irregular or stopped. Seek medical attention.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.

**Advice to doctor**            Treat symptomatically

## 5. FIRE FIGHTING MEASURES

**Specific Hazards**            Flammable liquid. Avoid all ignition sources. Do not smoke.

**Extinguishing Media**        On burning will emit toxic fumes. Use foam, dry chemical, carbon dioxide.

**Fire fighting advice**        Avoid contamination with oxidising agents. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

**Minor Spills**                Clean up all spills immediately. Place in a suitable labelled container for waste disposal.

**Major Spills**                Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

**Handling**                    Avoid contact with skin and eyes. Wear protective clothing, gloves and safety glasses. Use in only well ventilated areas. Avoid breathing vapour or spray mists. Avoid physical damage to containers. Always wash hands with soap and water after handling.

**Storage**                     Store in cool, dry, well-ventilated area out of direct sunlight and away from sources of ignition. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Have appropriate fire extinguishers in and near storage area. Reference Australian Standard AS1940-The storage and handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits**    No exposure limits set by Safe Work Australia. However, Exposure Standard(s) for constituent(s):

Mineral Turps:                    8hr TWA = 480mg/m<sup>3</sup>

**Engineering Control Measures**    Use under well ventilated conditions to keep airborne levels below exposure limits. If used indoors, open all windows and doors. If natural ventilation is inadequate, a flameproof local exhaust system is required. Close containers when not in use.

**Respiratory Protection**    If engineering controls insufficient to control airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian Standard AS/NZS1715 – Selection, use and maintenance of Respiratory protection devices; and AS/NZS 1716 – Respiratory Protective Devices to suit the individual use circumstances.

**Eye Protection**            Safety glasses with side shields or chemical goggles should be worn. Reference Australian Standard AS/NZS 1337 – Eye Protector for Industrial Applications to suit individual use circumstances.

**Hand Protection**            Wear impervious gloves (Nitrile, Neoprene) or other suitable gloves conforming to AS/NZS 2161 – Occupational protective gloves. Wash hands prior to smoking, eating and drinking.

**Body Protection**            Suitable protective work wear, e.g. cotton overalls conforming to AS/NZS 2919 – industrial clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Viscous Liquid	<b>Flammability Limits</b>	Not Available
<b>Odour</b>	Solvent hydrocarbon	<b>Solubility in water</b>	Insoluble in water. Soluble in organic solvents
<b>Colour</b>	White	<b>Flash Point</b>	>23 <sup>o</sup> C
<b>Boiling Point</b>	Not Applicable	<b>Vapour pressure (20<sup>o</sup>C)</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Evaporation rate</b>	Not Available
<b>Specific Gravity</b>	1.1 – 1.2 at 25 <sup>o</sup> C	<b>Auto-ignition Temp(C)</b>	Not Available
		<b>Volatile (%Wt.)</b>	60-70%%

**10. STABILITY AND REACTIVITY**

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling
<b>Incompatible Materials</b>	Incompatible with strong oxidising agents and acids
<b>Hazardous Decomposition Products</b>	May cause hazardous fumes when undergoing decomposition. Fumes may contain Carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of any metals listed in section 3.
<b>Hazardous Polymerisation</b>	Will not occur
<b>Chemical Stability</b>	Stable under normal conditions of storage and handling

**11. TOXICOLOGICAL INFORMATION**

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Acute symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting
<b>Chronic Effects</b>	Prolonged and repeated breathing of spray mist and/or sanding dust over a period of years may cause dust disease of lungs kidney and/or liver damage.

**12. ECOLOGICAL INFORMATION**

<b>Ecotoxicity</b>	Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environments
<b>Degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulation</b>	Not available
<b>Environmental Protection</b>	Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION**

Road and Rail		Marine		Air	
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.		Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.		Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.	
<b>UN No</b>	1263	<b>UN No</b>	1263	<b>UN No:</b>	1263
<b>Class-primary</b>	3 Flammable Liquid	<b>Class-primary</b>	3 Flammable Liquid		
<b>Packing Group</b>	111	<b>Packing Group</b>	111	<b>Packing Group:</b>	111
<b>Proper Shipping Name</b>	PAINT	<b>Proper Shipping Name</b>	PAINT	<b>Proper Shipping Name</b>	PAINT
<b>Hazchem Code</b>	3Y			<b>UN No:</b>	1263

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as hazardous according to criteria of Safe Work Australia. Xi: Irritant
<b>Poisons Schedule</b>	S6
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	R11: Highly Flammable R37: Irritating to respiratory system R66: Repeated exposure may cause skin dryness or cracking R67: Vapours may cause drowsiness or dizziness R51/53: Toxic to aquatic organisms, may cause long term adverse effects in aquatic environment.
<b>Safety Phrase(s)</b>	S2: Keep out of reach of children S16: Keep away from ignition source – no smoking S23: Do not breathe vapour/mist/spray S24/25: Avoid contact with skin and eyes S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this SDS or container label.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints (Aust) Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 958-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.1</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX SEMI GLOSS ENAMEL</b>
<b>Product Code</b>	<b>958 -100</b>
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Use as a decorative & protective coating on timber structures. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

This material is **Hazardous** according to criteria of Safe Work Australia.  
Classified as **Dangerous Goods** by the criteria of the Australian Dangerous Goods Code for transport by Road & Rail.

<b>Risk Phrases</b>	Xi: Flammable. Irritating to skin
<b>Safety Phrases</b>	Keep out of reach of children, do not breathe vapour, and avoid contact with skin and eyes. If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Poisons Schedule</b>	None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion</b>
	Kerosene	8008-20-6	0-10%
	Mineral Turps		10-20%
	Pigments		20-30%
	Synthetic Pigments		20-40%
	Other ingredients not deemed to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Apply air resuscitation if breathing is irregular or stopped. Seek medical attention.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	Flammable liquid. Avoid all ignition sources. Do not smoke.
<b>Extinguishing Media</b>	On burning will emit toxic fumes. Use foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Avoid contamination with oxidising agents. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Avoid contact with skin and eyes. Wear protective clothing, gloves and safety glasses. Use in only well ventilated areas. Avoid breathing vapour or spray mists. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool, dry, well-ventilated area out of direct sunlight and away from sources of ignition. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Have appropriate fire extinguishers in and near storage area. Reference Australian Standard AS1940-The storage and handling of flammable and combustible liquids.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Occupational Exposure Limits</b>	No exposure limits set by Safe Work Australia. However, Exposure Standard(s) for constituent(s): Mineral Turps: 8hr TWA = 480mg/m <sup>3</sup>
<b>Engineering Control Measures</b>	Use under well ventilated conditions to keep airborne levels below exposure limits. If used indoors, open all windows and doors. If natural ventilation is inadequate, a flameproof local exhaust system is required. Close containers when not in use.
<b>Respiratory Protection</b>	If engineering controls insufficient to control airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian Standard AS/NZS1715 – Selection, use and maintenance of Respiratory protection devices; and AS/NZS 1716 – Respiratory Protective Devices to suit the individual use circumstances.
<b>Eye Protection</b>	Safety glasses with side shields or chemical goggles should be worn. Reference Australian Standard AS/NZS 1337 – Eye Protector for Industrial Applications to suit individual use circumstances.
<b>Hand Protection</b>	Wear impervious gloves (Nitrile, Neoprene) or other suitable gloves conforming to AS/NZS 2161 – Occupational protective gloves. Wash hands prior to smoking, eating and drinking.
<b>Body Protection</b>	Suitable protective work wear, e.g. cotton overalls conforming to AS/NZS 2919 – industrial clothing.



**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Viscous Liquid	<b>Flammability Limits</b>	Not Available
<b>Odour</b>	Solvent hydrocarbon	<b>Solubility in water</b>	Insoluble in water. Soluble in organic solvents
<b>Colour</b>	White	<b>Flash Point</b>	>23 <sup>o</sup> C
<b>Boiling Point</b>	Not Applicable	<b>Vapour pressure (20<sup>o</sup>C)</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Evaporation rate</b>	Not Available
<b>Specific Gravity</b>	1.3 – 1.4 at 25 <sup>o</sup> C	<b>Auto-ignition Temp(C)</b>	Not Available
		<b>Volatile (%Wt.)</b>	65-75%

**10. STABILITY AND REACTIVITY**

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling
<b>Incompatible Materials</b>	Incompatible with strong oxidising agents and acids
<b>Hazardous Decomposition Products</b>	May cause hazardous fumes when undergoing decomposition. Fumes may contain Carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of any metals listed in section 3.
<b>Hazardous Polymerisation</b>	Will not occur
<b>Chemical Stability</b>	Stable under normal conditions of storage and handling

**11. TOXICOLOGICAL INFORMATION**

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Acute symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting
<b>Chronic Effects</b>	Prolonged and repeated breathing of spray mist and/or sanding dust over a period of years may cause dust disease of lungs kidney and/or liver damage.

**12. ECOLOGICAL INFORMATION**

<b>Ecotoxicity</b>	Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environments
<b>Degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulation</b>	Not available
<b>Environmental Protection</b>	Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION**

<b>Road and Rail</b>		<b>Marine</b>		<b>Air</b>	
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.		Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.		Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.	
<b>UN No</b>	1263	<b>UN No</b>	1263	<b>UN No:</b>	1263
<b>Class-primary</b>	3 Flammable Liquid	<b>Class-primary</b>	3 Flammable Liquid		
<b>Packing Group</b>	111	<b>Packing Group</b>	111	<b>Packing Group:</b>	111
<b>Proper Shipping Name</b>	PAINT	<b>Proper Shipping Name</b>	PAINT	<b>Proper Shipping Name</b>	PAINT
<b>Hazchem Code</b>	3Y			<b>UN No:</b>	1263

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as hazardous according to criteria of Safe Work Australia. Xi: Irritant
<b>Poisons Schedule</b>	S6
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	R11: Highly Flammable R37: Irritating to respiratory system R66: Repeated exposure may cause skin dryness or cracking R67: Vapours may cause drowsiness or dizziness R51/53: Toxic to aquatic organisms, may cause long term adverse effects in aquatic environment.
<b>Safety Phrase(s)</b>	S2: Keep out of reach of children S16: Keep away from ignition source – no smoking S23: Do not breathe vapour/mist/spray S24/25: Avoid contact with skin and eyes S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS or container label.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints (Aust) Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 959-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.1</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX OIL BASED UNDERCOAT</b>
<b>Product Code</b>	<b>959 -100</b>
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Use as a decorative & protective coating on timber structures. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

This material is **Hazardous** according to criteria of Safe Work Australia.  
Classified as **Dangerous Goods** by the criteria of the Australian Dangerous Goods Code for transport by Road & Rail.

<b>Risk Phrases</b>	Xi: Flammable. Irritating to skin
<b>Safety Phrases</b>	Keep out of reach of children, do not breathe vapour, and avoid contact with skin and eyes. If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Poisons Schedule</b>	None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b><u>Name</u></b>	<b><u>CAS Number</u></b>	<b><u>Proportion</u></b>
	Kerosene	8008-20-6	0-5%
	Mineral Turps		0-15%
	Synthetic Polymer		10-20%
	Pigments		40-60%
	Other ingredients determined not to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Apply air resuscitation if breathing is irregular or stopped. Seek medical attention.
<b>First Aid Facilities</b>	Eye wash and safety shower facilities should be available.
<b>Advice to doctor</b>	Treat symptomatically

**5. FIRE FIGHTING MEASURES**

<b>Specific Hazards</b>	Flammable liquid. Avoid all ignition sources. Do not smoke.
<b>Extinguishing Media</b>	On burning will emit toxic fumes. Use foam, dry chemical, carbon dioxide.
<b>Fire fighting advice</b>	Avoid contamination with oxidising agents. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Minor Spills</b>	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
<b>Major Spills</b>	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Avoid contact with skin and eyes. Wear protective clothing, gloves and safety glasses. Use in only well ventilated areas. Avoid breathing vapour or spray mists. Avoid physical damage to containers. Always wash hands with soap and water after handling.
<b>Storage</b>	Store in cool, dry, well-ventilated area out of direct sunlight and away from sources of ignition. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Have appropriate fire extinguishers in and near storage area. Reference Australian Standard AS1940-The storage and handling of flammable and combustible liquids.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Occupational Exposure Limits</b>	No exposure limits set by Safe Work Australia. However, Exposure Standard(s) for constituent(s): Mineral Turps: 8hr TWA = 480mg/m <sup>3</sup>
<b>Engineering Control Measures</b>	Use under well ventilated conditions to keep airborne levels below exposure limits. If used indoors, open all windows and doors. If natural ventilation is inadequate, a flameproof local exhaust system is required. Close containers when not in use.
<b>Respiratory Protection</b>	If engineering controls insufficient to control airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian Standard AS/NZS1715 – Selection, use and maintenance of Respiratory protection devices; and AS/NZS 1716 – Respiratory Protective Devices to suit the individual use circumstances.
<b>Eye Protection</b>	Safety glasses with side shields or chemical goggles should be worn. Reference Australian Standard AS/NZS 1337 – Eye Protector for Industrial Applications to suit individual use circumstances.
<b>Hand Protection</b>	Wear impervious gloves (Nitrile, Neoprene) or other suitable gloves conforming to AS/NZS 2161 – Occupational protective gloves. Wash hands prior to smoking, eating and drinking.
<b>Body Protection</b>	Suitable protective work wear, e.g. cotton overalls conforming to AS/NZS 2919 – industrial clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Viscous Liquid	<b>Flammability Limits</b>	Not Available
<b>Odour</b>	Solvent hydrocarbon	<b>Solubility in water</b>	Insoluble in water. Soluble in organic solvents
<b>Colour</b>	White	<b>Flash Point</b>	>23 <sup>o</sup> C
<b>Boiling Point</b>	Not Applicable	<b>Vapour pressure (20<sup>o</sup>C)</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Evaporation rate</b>	Not Available
<b>Specific Gravity</b>	1.5 – 1.6 at 25 <sup>o</sup> C	<b>Auto-ignition Temp(C)</b>	Not Available
		<b>Volatile (%Wt.)</b>	70-80%%

**10. STABILITY AND REACTIVITY**

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling
<b>Incompatible Materials</b>	Incompatible with strong oxidising agents and acids
<b>Hazardous Decomposition Products</b>	May cause hazardous fumes when undergoing decomposition. Fumes may contain Carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of any metals listed in section 3.
<b>Hazardous Polymerisation</b>	Will not occur
<b>Chemical Stability</b>	Stable under normal conditions of storage and handling

**11. TOXICOLOGICAL INFORMATION**

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Acute symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting
<b>Chronic Effects</b>	Prolonged and repeated breathing of spray mist and/or sanding dust over a period of years may cause dust disease of lungs kidney and/or liver damage.

**12. ECOLOGICAL INFORMATION**

<b>Ecotoxicity</b>	Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environments
<b>Degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulation</b>	Not available
<b>Environmental Protection</b>	Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

**13. DISPOSAL CONSIDERATIONS**

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**COLOURTREND PAINTS AUSTRALIA PTY LTD - SDS****Product Code: 959-100****Issue Date: 26/02/2015****Issue No.1****14. TRANSPORT INFORMATION**

<b>Road and Rail</b>		<b>Marine</b>		<b>Air</b>	
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.		Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.		Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.	
<b>UN No</b>	1263	<b>UN No</b>	1263	<b>UN No:</b>	1263
<b>Class-primary</b>	3 Flammable Liquid	<b>Class-primary</b>	3 Flammable Liquid		
<b>Packing Group</b>	111	<b>Packing Group</b>	111	<b>Packing Group:</b>	111
<b>Proper Shipping Name</b>	PAINT	<b>Proper Shipping Name</b>	PAINT	<b>Proper Shipping Name</b>	PAINT
<b>Hazchem Code</b>	3Y			<b>UN No:</b>	1263

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as hazardous according to criteria of Safe Work Australia. Xi: Irritant
<b>Poisons Schedule</b>	S6
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	R11: Highly Flammable R37: Irritating to respiratory system R66: Repeated exposure may cause skin dryness or cracking R67: Vapours may cause drowsiness or dizziness R51/53: Toxic to aquatic organisms, may cause long term adverse effects in aquatic environment.
<b>Safety Phrase(s)</b>	S2: Keep out of reach of children S16: Keep away from ignition source – no smoking S23: Do not breathe vapour/mist/spray S24/25: Avoid contact with skin and eyes S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS or container label.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints (Aust) Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.



<b>Product Code: 961-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Name</b>	<b>COVERMAX QUICK DRY UNDERCOAT</b>
<b>Product Code</b>	<b>961-100</b>
<b>Company Name</b>	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
<b>Address</b>	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
<b>Phone</b>	02 97562400
<b>Fax</b>	02 97562405
<b>Emergency</b>	0439 624 009
<b>Product Use</b>	Use as a decorative & protective coating on timber structures. Applied by brush, roller, conventional spray or airless spray.

**2. HAZARDS IDENTIFICATION**

This material is **Hazardous** according to criteria of Safe Work Australia.  
Classified as **Dangerous Goods** by the criteria of the Australian Dangerous Goods Code for transport by Road & Rail.

<b>Risk Phrases</b>	Xi: Flammable. Irritating to skin
<b>Safety Phrases</b>	Keep out of reach of children, do not breathe vapour, and avoid contact with skin and eyes. If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Poisons Schedule</b>	None allocated

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Characterisation</b>	Liquid		
<b>Ingredients</b>	<b><u>Name</u></b>	<b><u>CAS Number</u></b>	<b><u>Proportion</u></b>
	Kerosene	8008-20-6	<10%
	White Spirit	8052-41-3	10-30%
	Mineral Turps		10-30%
	Xylene	1330-20-7	<10%
	Pigments		30-60%
	Synthetic Polymer		10-30%
	Other ingredients determined not to be hazardous		to 100%

**4. FIRST AID MEASURES**

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

<b>Swallowed</b>	If swallowed, DO NOT induce vomiting, seek medical attention immediately.
<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
<b>Skin</b>	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.
<b>Inhaled</b>	Remove from contaminated area. Remove contaminated clothing. Apply air resuscitation if breathing is irregular or stopped. Seek medical attention.

**First Aid Facilities** Eye wash and safety shower facilities should be available.

**Advice to doctor** Treat symptomatically

## 5. FIRE FIGHTING MEASURES

**Specific Hazards** Flammable liquid. Avoid all ignition sources. Do not smoke.

**Extinguishing Media** On burning will emit toxic fumes. Use foam, dry chemical, carbon dioxide.

**Fire fighting advice** Avoid contamination with oxidising agents. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

**Minor Spills** Clean up all spills immediately. Place in a suitable labelled container for waste disposal.

**Major Spills** Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin and eyes. Wear protective clothing, gloves and safety glasses. Use in only well ventilated areas. Avoid breathing vapour or spray mists. Avoid physical damage to containers. Always wash hands with soap and water after handling.

**Storage** Store in cool, dry, well-ventilated area out of direct sunlight and away from sources of ignition. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Have appropriate fire extinguishers in and near storage area. Reference Australian Standard AS1940-The storage and handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits** No exposure limits set by Safe Work Australia. However, Exposure Standard(s) for constituent(s):

White Spirit: 8hr TWA = 790mg/m<sup>3</sup>

Mineral Turps: 8hr TWA = 480mg/m<sup>3</sup>

Xylene: 8hr TWA = 350mg/m<sup>3</sup>

**Engineering Control Measures** Use under well ventilated conditions to keep airborne levels below exposure limits. If used indoors, open all windows and doors. If natural ventilation is inadequate, a flameproof local exhaust system is required. Close containers when not in use.

**Respiratory Protection** If engineering controls insufficient to control airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian Standard AS/NZS1715 – Selection, use and maintenance of Respiratory protection devices; and AS/NZS 1716 – Respiratory Protective Devices to suit the individual use circumstances.

**Eye Protection** Safety glasses with side shields or chemical goggles should be worn. Reference Australian Standard AS/NZS 1337 – Eye Protector for Industrial Applications to suit individual use circumstances.

**Hand Protection** Wear impervious gloves (Nitrile, Neoprene) or other suitable gloves conforming to AS/NZS 2161 – Occupational protective gloves. Wash hands prior to smoking, eating and drinking.

**Body Protection** Suitable protective work wear, e.g. cotton overalls conforming to AS/NZS 2919 –



industrial clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous Liquid	<b>Flammability Limits</b>	Not Available
<b>Odour</b>	Solvent hydrocarbon	<b>Solubility in water</b>	Insoluble in water. Soluble in organic solvents
<b>Colour</b>	White	<b>Flash Point</b>	>23°C
<b>Boiling Point</b>	Not Applicable	<b>Vapour pressure (20°C)</b>	Not Available
<b>Melting Point</b>	Not Available	<b>Evaporation rate</b>	Not Available
<b>Specific Gravity</b>	1.3 – 1.6 at 25°C	<b>Auto-ignition Temp(C)</b>	Not Available
		<b>Volatile (%Wt.)</b>	28%

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling
<b>Incompatible Materials</b>	Incompatible with strong oxidising agents and acids
<b>Hazardous Decomposition Products</b>	May cause hazardous fumes when undergoing decomposition. Fumes may contain Carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of any metals listed in section 3.
<b>Hazardous Polymerisation</b>	Will not occur
<b>Chemical Stability</b>	Stable under normal conditions of storage and handling

## 11. TOXICOLOGICAL INFORMATION

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Acute symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Eye</b>	May produce eye irritation
<b>Skin</b>	Contact with skin may results in irritation
<b>Inhaled</b>	The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.
<b>Swallowed</b>	Swallow may result in nausea, abdominal irritation and vomiting
<b>Chronic Effects</b>	Prolonged and repeated breathing of spray mist and/or sanding dust over a period of years may cause dust disease of lungs kidney and/or liver damage.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environments
<b>Degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulation</b>	Not available
<b>Environmental Protection</b>	Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

## 13. DISPOSAL CONSIDERATIONS

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

**14. TRANSPORT INFORMATION**

Road and Rail	Marine	Air
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.	Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.	Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
<b>UN No</b> 1263	<b>UN No</b> 1263	<b>UN No:</b> 1263
<b>Class-primary</b> 3 Flammable Liquid	<b>Class-primary</b> 3 Flammable Liquid	
<b>Packing Group</b> 111	<b>Packing Group</b> 111	<b>Packing Group:</b> 111
<b>Proper Shipping Name</b> PAINT	<b>Proper Shipping Name</b> PAINT	<b>Proper Shipping Name</b> PAINT
<b>Hazchem Code</b> 3Y		<b>UN No:</b> 1263

**15. REGULATORY INFORMATION**

<b>Classification</b>	Classified as hazardous according to criteria of Safe Work Australia. Xi: Irritant
<b>Poisons Schedule</b>	S6
<b>A.I.C.S. Status</b>	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Risk Phrase(s)</b>	R11: Highly Flammable R37: Irritating to respiratory system R66: Repeated exposure may cause skin dryness or cracking R67: Vapours may cause drowsiness or dizziness R51/53: Toxic to aquatic organisms, may cause long term adverse effects in aquatic environment.
<b>Safety Phrase(s)</b>	S2: Keep out of reach of children S16: Keep away from ignition source – no smoking S23: Do not breathe vapour/mist/spray S24/25: Avoid contact with skin and eyes S36/37/39: Wear suitable protective clothing, gloves and eye/face protection S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS or container label.

**16. OTHER INFORMATION**

This safety data sheet prepared by Colourtrend Paints (Aust) Pty Ltd summarizes our knowledge of the health and safety hazard information for this product including best practice handling information for the workplace. We do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Each user should read this SDS and consider the information in the context of how the product may be handled, including any equipment, technique or material mentioned and should consider appropriate risk assessment to satisfy that all applicable safety and health standards can be met.

<b>Product Code: 951-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**CoverMax Ceiling Flat**

<b>Product Description</b>	CoverMax Ceiling Flat is specially designed to give a high opacity, dead flat appearance. It is ideal for interior ceilings and is easy to apply without messy spatter.
<b>Areas of Use</b>	Suitable for ceilings
<b>Australian Standards</b>	AS 2311 The Painting of Buildings APAS 0260/5
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.
<b>Volume Solids</b>	26%
<b>Clean Up</b>	Water
<b>Application</b>	Brush, roller or spray Stir well before use using a broad flat paddle in a scooping motion. <b>Spray:</b> Satisfactory with most equipment. Observe the State Spray Painting Regulations
<b>Drying</b> (25 <sup>o</sup> C & 50% RH)	Dry to touch – 30 minutes Recoat – 1-2 hours @ 25 <sup>o</sup> C In damp, cool or humid conditions, drying may be extended. The temperature should be above 10 <sup>o</sup> C during application and drying.
<b>Coverage</b>	Approximately 14 square metres per litre. Coverage will vary depending on the profile and porosity of the surface. Dry Film Thickness – 22 microns Wet Film Thickness – 80 microns
<b>Colour</b>	White
<b>Surface Preparation</b>	<b><u>Previously Painted</u></b> <ul style="list-style-type: none"> <li>• Ensure surface to be painted is sound. (see Soundness)</li> <li>• Remove all soft, powdered, blistered, loose or flaking paint.</li> <li>• Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation.</li> <li>• Wash with clean water and allow surface to dry.</li> <li>• Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.</li> </ul> <b><u>Soundness</u></b> Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an “X” with a sharp blade, press a piece of clear tape over the “X” as firmly as possible with the ball of the thumb then as

quickly as possible, tear off the tape in one movement. Any evidence of the paint film adhering to the tape is indicative of an unsound surface and it must be removed before repainting. This process should be carried out at several locations to test the entire surface.

**Note** Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Wear dust mask if sanding down
- Wear protective clothing
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains

Dispose of waste using authorised collection procedures. Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

<b>Product Code: 952-100</b>	<b>Issue Date: 1/08/2012</b>	<b>Issue No.1</b>
------------------------------	------------------------------	-------------------

**CoverMax Acrylic Sealer Undercoat**

<b>Product Description</b>	CoverMax Acrylic Sealer Undercoat is specially designed for use on interior and exterior surfaces to give long lasting performance. It is easy to apply without messy spatter.
<b>Areas of Use</b>	Suitable for interior and exterior surfaces. Suitable for masonry, plaster, plasterboard, fibro, paper-faced wallboards and appropriately primed metal.
<b>Australian Standards</b>	AS 2311 The Painting of Buildings APAS 0172
<b>Components</b>	Pigment – Durable, Non Lead Binder – Acrylic Styrene polymer Solvent – Water
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.
<b>Volume Solids</b>	33%
<b>Clean Up</b>	Water
<b>Application</b>	Brush, roller or spray Stir well before use using a broad flat paddle in a scooping motion.  Check weather forecasts and <b>do not</b> paint where forecasts indicate that; <ul style="list-style-type: none"> <li>o Rain is imminent;</li> <li>o The temperature is likely to fall below 10°C or relative humidity will exceed 80%.</li> <li>o In hot dry conditions commence painting in an area away from direct sunlight; thinning with 10% water can assist application.</li> </ul> <b>Spray:</b> Satisfactory with most equipment. Observe the State Spray Painting Regulations
<b>Drying</b> (25°C & 50% RH)	Dry to touch – 30 minutes Recoat – 1-2 hours @ 25°C
<b>Coverage</b>	In damp, cool or humid conditions, drying may be extended. Approximately 14 square metres per litre. Coverage will vary depending on the profile and porosity of the surface.  Dry Film Thickness – 21 microns Wet Film Thickness – 63 microns
<b>Colour</b>	White
<b>Surface Preparation</b>	<b><u>Previously Painted</u></b> <ul style="list-style-type: none"> <li>• Ensure surface to be painted is sound. (see Soundness)</li> <li>• Remove all soft, powdered, blistered, loose or flaking paint.</li> <li>• Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation.</li> <li>• Wash with clean water and allow surface to dry.</li> <li>• Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.</li> <li>• Spot prime bare/repared areas with CoverMax Acrylic Sealer Undercoat. Apply one full coat of CoverMax Acrylic Sealer Undercoat followed by finish coats.</li> </ul>

**Soundness**

Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. Any evidence of the paint film adhering to the tape is indicative of an unsound surface and it must be removed before repainting. This process should be carried out at several locations to test the entire surface.

**Unpainted Brick, Masonry, Cement Render and Fibre Cement**

- Ensure surface to be painted is free from all contaminants, including mould, moss, lichen, efflorescence etc.
- Dust off and apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats.
  - Cement Render must be allowed to cure for 14-28 days prior to application of CoverMax Acrylic Sealer Undercoat. Substrates should contain less than 15% (wood equivalent) moisture before application.
  - The application of a second coat of CoverMax Acrylic Sealer Undercoat will assist in evening out varying surface textures.
- For Set Plaster and Plaster glass, use Binder Sealer.

**Galvanised Steel, Zinalume®, Aluminium**

- New Zinalume®, Galvanised Iron and Aluminium may be left to weather prior to painting. If it is to be painted immediately then surface should be cleaned down using Mineral Turps and non metallic scourers.
- Surface should be primed with appropriate metal primer.
- Apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats.

**Timber-New**

- Interior
  - Fill all imperfections with appropriate filler and sand down.
  - Sand all dressed timber.
  - Dust down and apply one coat of CoverMax Acrylic Sealer Undercoat followed by selected finish coats.
- Exterior (Sheltered only)

Not recommended for timber in full exposure to sunlight

- Fill in imperfections with appropriate filler and sand down.
- Dust down and apply one coat of Wood Primer
- Then apply one coat of CoverMax Acrylic Sealer Undercoat followed by selected finish coats.

**Note** Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Wear dust mask if sanding down
- Wear protective clothing.
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains  
Dispose of waste using authorised collection procedures. Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

Product Code: 953-100	Issue Date: 26/02/2015	Issue No.2
-----------------------	------------------------	------------

**CoverMax Acrylic Low Sheen**

<b>Product Description</b>	CoverMax Acrylic Low Sheen is suitable for interior and exterior surfaces. This product designed to give good washability with a smooth elegant appearance and long lasting serviceable qualities.
<b>Areas of Use</b>	Suitable for interior and exterior wall surfaces. Recommended for masonry, plaster, plasterboard, fibro, paper-faced wallboards and appropriately primed metal. Not recommended for exterior timber substrates.
<b>Special Features</b>	<ul style="list-style-type: none"> <li>• Water based</li> <li>• Interior/Exterior</li> <li>• Recoat in 2 hours</li> <li>• Resists mould and fungal growth</li> </ul>
<b>Australian Standards</b>	AS 2311 The Painting of Buildings APAS 0260/3
<b>Components</b>	Pigment – Durable, Non Lead Binder – Acrylic Styrene polymer Solvent – Water
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.
<b>Volume Solids</b>	34%
<b>Clean Up</b>	Water
<b>Application</b>	Brush, roller or spray Stir well before use using a broad flat paddle in a scooping motion. Check weather forecasts and <b>do not</b> paint where forecasts indicate that; <ul style="list-style-type: none"> <li>• Rain is imminent;</li> <li>• The temperature is likely to fall below 10°C or relative humidity will exceed 80%.</li> <li>• In hot dry conditions commence painting in an area away from direct sunlight; thinning with 5% water can assist application.</li> </ul> <b>Spray:</b> Satisfactory with most equipment. Observe the State Spray Painting Regulations
<b>Drying</b> (25°C & 50% RH)	Dry to touch – 30 minutes Recoat – 1-2 hours @ 25°C In damp, cool or humid conditions, drying may be extended.
<b>Coverage</b>	Approximately 14-16 square metres per litre. Coverage will vary depending on the profile and porosity of the surface. Dry Film Thickness – 21 microns Wet Film Thickness – 63 microns

**Colour** White (tintable to pastel colour shades)

**Surface** Previously Painted

**Preparation**

- Ensure surface to be painted is sound. (see Soundness)
- Remove all soft, powdered, blistered, loose or flaking paint.
- Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation.
- Wash with clean water and allow surface to dry.
- Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.
- Spot prime bare/repaired areas with Acrylic Sealer Undercoat. Apply one full coat of Sealer Undercoat followed by finish coats of CoverMax Acrylic Low Sheen.

**Soundness**

Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. Any evidence of the paint film adhering to the tape is indicative of an unsound surface and it must be removed before repainting. This process should be carried out at several locations to test the entire surface.

**Unpainted Brick, Masonry, Cement Render and Fibre Cement**

- Ensure surface to be painted is free from all contaminants, including mould, moss, lichen, efflorescence etc.
- Dust off and apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Acrylic Low Sheen.
  - Cement Render must be allowed to cure for 28 days. Substrates should contain less than 15% (wood equivalent) moisture before application.

**Galvanised Steel, Zinalume®, Aluminium**

- Surface should be primed with appropriate metal primer.
- Apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Acrylic Low Sheen.

**Timber-New**

- Interior
  - Fill all imperfections with appropriate filler and sand down.
  - Sand all dressed timber.
  - Dust down and apply one coat of Acrylic Sealer Undercoat followed by finish coats of CoverMax Acrylic Low Sheen.
- Exterior (Sheltered only)

Not recommended for timber in full exposure to sunlight or other substrates subject to large movement.



**Note** Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Wear dust mask if sanding down
- Wear protective clothing.
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains  
 Dispose of waste using authorised collection procedures. Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

<b>Product Code: 954-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.2</b>
------------------------------	-------------------------------	-------------------

**CoverMax Acrylic Satin**

<b>Product Description</b>	CoverMax Acrylic Satin is suitable for interior and exterior surfaces. This product designed to give good washability with a smooth elegant appearance and long lasting serviceable qualities.
<b>Areas of Use</b>	Suitable for interior and exterior wall surfaces. Recommended for masonry, plaster, plasterboard, fibro, paper-faced wallboards and appropriately primed metal. Not recommended for exterior timber substrates.
<b>Special Features</b>	<ul style="list-style-type: none"> <li>• Water based</li> <li>• Interior/Exterior</li> <li>• Recoat in 2 hours</li> <li>• Resists mould and fungal growth</li> </ul>
<b>Australian Standards</b>	AS 2311 The Painting of Buildings APAS 0260/2
<b>Components</b>	Pigment – Durable, Non Lead Binder – Acrylic Styrene polymer Solvent – Water
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.
<b>Volume Solids</b>	36%
<b>Clean Up</b>	Water
<b>Application</b>	Brush, roller or spray Stir well before use using a broad flat paddle in a scooping motion. Check weather forecasts and <b>do not</b> paint where forecasts indicate that; <ul style="list-style-type: none"> <li>• Rain is imminent;</li> <li>• The temperature is likely to fall below 10°C or relative humidity will exceed 80%.</li> <li>• In hot dry conditions commence painting in an area away from direct sunlight; thinning with 5% water can assist application.</li> </ul> <b>Spray:</b> Satisfactory with most equipment. Observe the State Spray Painting Regulations
<b>Drying</b> (25°C & 50% RH)	Dry to touch – 30 minutes Recoat – 1-2 hours @ 25°C In damp, cool or humid conditions, drying may be extended.
<b>Coverage</b>	Approximately 14-16 square metres per litre. Coverage will vary depending on the profile and porosity of the surface. Dry Film Thickness – 23 microns Wet Film Thickness – 65 microns

**Colour** White (tintable to pastel colour shades)

**Surface** Previously Painted

**Preparation**

- Ensure surface to be painted is sound. (see Soundness)
- Remove all soft, powdered, blistered, loose or flaking paint.
- Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation.
- Wash with clean water and allow surface to dry.
- Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.
- Spot prime bare/repared areas with Acrylic Sealer Undercoat. Apply one full coat of Sealer Undercoat followed by finish coats of CoverMax Acrylic Satin.

**Soundness**

Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. Any evidence of the paint film adhering to the tape is indicative of an unsound surface and it must be removed before repainting. This process should be carried out at several locations to test the entire surface.

**Unpainted Brick, Masonry, Cement Render and Fibre Cement**

- Ensure surface to be painted is free from all contaminants, including mould, moss, lichen, efflorescence etc.
- Dust off and apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Acrylic Satin.
  - Cement Render must be allowed to cure for 28 days. Substrates should contain less than 15% (wood equivalent) moisture before application.

**Galvanised Steel, Zinalume®, Aluminium**

- Surface should be primed with appropriate metal primer.
- Apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Acrylic Satin.

**Timber-New**

- Interior
  - Fill all imperfections with appropriate filler and sand down.
  - Sand all dressed timber.
  - Dust down and apply one coat of Acrylic Sealer Undercoat followed by finish coats of CoverMax Acrylic Satin.
- Exterior (Sheltered only)

Not recommended for timber in full exposure to sunlight or other substrates subject to large movement.

**Note** Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Wear dust mask if sanding down
- Wear protective clothing.
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains  
Dispose of waste using authorised collection procedures. Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

<b>Product Code: 955-100</b>	<b>Issue Date: 26/02/2015</b>	<b>Issue No.1</b>
------------------------------	-------------------------------	-------------------

**CoverMax Matt Acrylic**

<b>Product Description</b>	CoverMax Matt Acrylic is suitable for interior surfaces. This product was designed to give good washability with a smooth elegant appearance and long lasting serviceable qualities.
<b>Areas of Use</b>	Suitable for interior wall surfaces. Recommended for masonry, plaster, plasterboard, fibro, paper-faced wallboards and appropriately primed metal. Not recommended for exterior timber substrates.
<b>Special Features</b>	<ul style="list-style-type: none"> <li>• Water based</li> <li>• Interior</li> <li>• Recoat in 2 hours</li> <li>• Resists mould and fungal growth</li> </ul>
<b>Australian Standards</b>	AS 2311 The Painting of Buildings APAS 0260/4
<b>Components</b>	Pigment – Durable, Non Lead Binder – Acrylic Styrene polymer Solvent – Water
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.
<b>Volume Solids</b>	37%
<b>Clean Up</b>	Water
<b>Application</b>	Brush, roller or spray  Stir well before use using a broad flat paddle in a scooping motion.  Check weather forecasts and <b>do not</b> paint where forecasts indicate that; <ul style="list-style-type: none"> <li>• Rain is imminent</li> <li>• The temperature is likely to fall below 10°C or relative humidity will exceed 80%.</li> <li>• In hot dry conditions commence painting in an area away from direct sunlight; thinning with 5% water can assist application.</li> </ul> <b>Spray:</b> Satisfactory with most equipment. Observe the State Spray Painting Regulations
<b>Drying</b> (25°C & 50% RH)	Dry to touch – 30 minutes  Recoat – 1-2 hours @ 25°C  In damp, cool or humid conditions, drying may be extended.
<b>Coverage</b>	Approximately 14-16 square metres per litre.  Coverage will vary depending on the profile and porosity of the surface.  Dry Film Thickness – 25 microns

Wet Film Thickness – 67 microns

**Colour** White (tintable to pastel colour shades)

**Surface** Previously Painted

**Preparation**

- Ensure surface to be painted is sound. (see Soundness)
- Remove all soft, powdered, blistered, loose or flaking paint.
- Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation.
- Wash with clean water and allow surface to dry.
- Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.
- Spot prime bare/repaired areas with Acrylic Sealer Undercoat. Apply one full coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Matt Acrylic.

#### **Soundness**

Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an “X” with a sharp blade, press a piece of clear tape over the “X” as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. Any evidence of the paint film adhering to the tape is indicative of an unsound surface and it must be removed before repainting. This process should be carried out at several locations to test the entire surface.

#### **Unpainted Brick, Masonry, Cement Render and Fibre Cement**

- Ensure surface to be painted is free from all contaminants, including mould, moss, lichen, efflorescence etc.
- Dust off and apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Matt Acrylic.
  - Cement Render must be allowed to cure for 14-28 days. Substrates should contain less than 15% (wood equivalent) moisture before application.

#### **Galvanised Steel, Zinalume®, Aluminium**

- Surface should be primed with appropriate metal primer.
- Apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Matt Acrylic.

#### **Timber-New**

- Interior
  - Fill all imperfections with appropriate filler and sand down.
  - Sand all dressed timber.
  - Dust down and apply one coat of CoverMax Acrylic Sealer Undercoat followed by finish coats of CoverMax Matt Acrylic.
- Not recommended for timber in full exposure to sunlight or other substrates subject to large movement.

**Note** Mould, fungal infected surfaces and efflorescence must be treated

to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Wear dust mask if sanding down
- Wear protective clothing.
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains  
Dispose of waste using authorised collection procedures. Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

<b>Product Code: 956-100</b>	<b>Issue Date: 6/067/2013</b>	<b>Issue No.1</b>
------------------------------	-------------------------------	-------------------

**CoverMax Block Filler**

<b>Product Description</b>	CoverMax Block Filler is designed for use on interior and exterior surfaces. It is a heavy bodied, high solids filling coat to provide a smooth profile over rough substrates.						
<b>Areas of Use</b>	Suitable for interior and exterior surfaces brick and masonry surfaces. It is not recommended for timber or substrates prone to large expansion and contraction movements.						
<b>Australian Standards</b>	AS 2311 The Painting of Buildings						
<b>Components</b>	<table> <tr> <td>Pigment</td> <td>- Durable, Non Lead</td> </tr> <tr> <td>Binder</td> <td>- Styrene Acrylic polymer</td> </tr> <tr> <td>Solvent</td> <td>- Water</td> </tr> </table>	Pigment	- Durable, Non Lead	Binder	- Styrene Acrylic polymer	Solvent	- Water
Pigment	- Durable, Non Lead						
Binder	- Styrene Acrylic polymer						
Solvent	- Water						
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.						
<b>Volume Solids</b>	42%						
<b>Clean Up</b>	Water						
<b>Application</b>	<p>Brush, roller or spray            Stir well before use using a broad flat paddle in a scooping motion.</p> <p>Check weather forecasts and <b>do not</b> paint where forecasts indicate that;</p> <ul style="list-style-type: none"> <li>o Rain is imminent;</li> <li>o The temperature is likely to fall below 10°C or relative humidity will exceed 80%.</li> <li>o In hot dry conditions commence painting in an area away from direct sunlight; thinning with 10% water can assist application.</li> </ul> <p><b>Spray:</b> Satisfactory with most equipment. Observe the State Spray Painting Regulations</p>						
<b>Drying</b> (25°C & 50% RH)	<table> <tr> <td>Dry to touch</td> <td>- 30 minutes</td> </tr> <tr> <td>Recoat</td> <td>- 2 hours @ 25°C</td> </tr> </table> <p>In damp, cool or humid conditions, drying may be extended.</p>	Dry to touch	- 30 minutes	Recoat	- 2 hours @ 25°C		
Dry to touch	- 30 minutes						
Recoat	- 2 hours @ 25°C						
<b>Coverage</b>	<p>Approximately 8 square metres per litre.            Coverage will vary depending on the profile and porosity of the surface.</p> <table> <tr> <td>Dry Film Thickness</td> <td>- 25 microns</td> </tr> <tr> <td>Wet Film Thickness</td> <td>- 60 microns</td> </tr> </table>	Dry Film Thickness	- 25 microns	Wet Film Thickness	- 60 microns		
Dry Film Thickness	- 25 microns						
Wet Film Thickness	- 60 microns						
<b>Colour</b>	White						
<b>Surface Preparation</b>	<p><b><u>Previously Painted</u></b></p> <ul style="list-style-type: none"> <li>• Ensure surface to be painted is sound. (see Soundness)</li> <li>• Remove all soft, powdered, blistered, loose or flaking paint.</li> <li>• Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation.</li> <li>• Wash with clean water and allow surface to dry.</li> <li>• Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.</li> <li>• Spot prime bare/repared areas with CoverMax Block Filler. Apply one full coat of CoverMax Block Filler followed by finish coats.</li> </ul>						



**Soundness**

Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. Any evidence of the paint film adhering to the tape is indicative of an unsound surface and it must be removed before repainting. This process should be carried out at several locations to test the entire surface.

**Unpainted Brick, Masonry and Cement Render**

- Ensure surface to be painted is free from all contaminants, including mould, moss, lichen, efflorescence etc.
- Dust off and apply one coat of CoverMax Block Filler followed by finish coats.
  - Cement Render must be allowed to cure for 14-28 days prior to application of CoverMax Block Filler. Substrates should contain less than 15% (wood equivalent) moisture before application.
  - The application of a second coat of CoverMax Block Filler will assist in evening out varying surface textures.
- For Set Plaster and Plaster glass, use Binder Sealer. ..

**Note** Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Wear dust mask if sanding down
- Wear protective clothing.
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains  
Dispose of waste using authorised collection procedures. Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

Product Code: 957-100	Issue Date: 26/02/2015	Issue No.1
-----------------------	------------------------	------------

**CoverMax Gloss Enamel**

<b>Product Description</b>	CoverMax Gloss Enamel is premium quality oil based full gloss, weather resistant, interior/exterior enamel. It has been developed for easy brushing and long life protection on all exterior and interior surfaces. It wipes clean easily and is resistant to abrasions and hard knocks.						
<b>Areas of Use</b>	Doors, window frames, cupboards, weatherboards and all surfaces where a hard wearing full gloss finish is required.						
<b>Australian Standards</b>	AS 2311 The Painting of Buildings						
<b>Special Features</b>	<ul style="list-style-type: none"> <li>* Excellent Gloss</li> <li>* High Opacity</li> <li>* Outstanding flow and levelling</li> </ul>						
<b>Components</b>	<table> <tr> <td>Pigment</td> <td>– Durable, Non Lead</td> </tr> <tr> <td>Binder</td> <td>– Alkyd resin</td> </tr> <tr> <td>Solvent</td> <td>– Mineral Turpentine</td> </tr> </table>	Pigment	– Durable, Non Lead	Binder	– Alkyd resin	Solvent	– Mineral Turpentine
Pigment	– Durable, Non Lead						
Binder	– Alkyd resin						
Solvent	– Mineral Turpentine						
<b>Toxicity</b>	Dry paint is non-toxic but it is flammable. Conforms to AS1647, Part 3.						
<b>Flammability</b>	Product is flammable						
<b>Volume Solids</b>	52%						
<b>Thinning</b>	Mineral Turpentine – during hot dry conditions it may be necessary to thin with up to 50mL solvent per Litre.						
<b>Method of Application</b>	<p>Brush, roller or spray</p> <p>Stir well before use using a broad flat paddle in a scooping motion.</p> <p>Do not apply if temperature is below 10<sup>0</sup>C or likely to fall below 10<sup>0</sup>C during drying.</p> <p>Do not apply if rain is expected or in hot dry conditions.</p> <p><u>Spray</u> Satisfactory with most equipment. Observe the State Spray Painting Regulations</p>						
<b>Drying</b> (25 <sup>0</sup> C & 50% RH)	<table> <tr> <td>Dry to touch</td> <td>– 4 – 6 hours</td> </tr> <tr> <td>Recoat</td> <td>– 16 Hours</td> </tr> </table> <p>In damp, cool or humid conditions, drying may be extended.</p>	Dry to touch	– 4 – 6 hours	Recoat	– 16 Hours		
Dry to touch	– 4 – 6 hours						
Recoat	– 16 Hours						
<b>Coverage</b>	<p>Approximately 14-16 sq. metres per litre.</p> <p>Coverage will vary depending on the profile and surface porosity.</p> <table> <tr> <td>Dry Film Thickness</td> <td>– 33 microns</td> </tr> <tr> <td>Wet Film Thickness</td> <td>– 63 microns</td> </tr> </table>	Dry Film Thickness	– 33 microns	Wet Film Thickness	– 63 microns		
Dry Film Thickness	– 33 microns						
Wet Film Thickness	– 63 microns						

<b>Clean Up</b>	Mineral Turpentine
<b>Colour</b>	White
<b>Surface Preparation</b>	<p>Remove all soft, powdered, blistered, loose or flaking paint. Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation. Wash with clean water and allow for drying. Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.</p> <p>Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. If previous paint comes off it must be all removed.</p> <p><b><u>Timber New</u></b> Sand to remove all graying timber. Fill imperfection with appropriate filler and sand all dressed timber. Dust down and apply one coat of Wood Primer when dry, apply one coat of CoverMax Oil Based Undercoat then apply two tops coats of CoverMax Gloss Enamel, sanding lightly between coats.</p> <p><b><u>MDF New</u></b> Sand lightly, dust down and apply one coat of CoverMax Oil Based Undercoat, when dry apply two coats of CoverMax Gloss Enamel, sand lightly between coats.</p> <p><b><u>Brick, Masonry, Fibre Cement New</u></b> Ensure surface to be painted is free from mould, dirt, dust or any other contaminant. Fill imperfection with appropriate filler, sand down, dust off, and apply one coat of Binder Sealer. When dry apply two coats of CoverMax Gloss Enamel, sanding lightly between coats.</p> <p><b><u>Note:</u></b> Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.</p>
<b>Health and Safety</b>	<ul style="list-style-type: none"> <li>- Keep out of reach of children</li> <li>- Product is highly flammable</li> <li>- Wear dust mask if sanding down</li> <li>- Wear protective clothing.</li> <li>- Ensure good ventilation</li> <li>- Do not breathe vapour or spray</li> <li>- Wear eye protection</li> <li>- Store in a cool place</li> </ul>
<b>First Aid</b>	<ul style="list-style-type: none"> <li>- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.</li> <li>- If Swallowed- drink large amounts of water and seek medical attention.</li> </ul>
<b>Environment</b>	<p>Do not tip unused paint or washings down drains Dispose of waste using authorised collection procedures.</p>

Product Code: 958-100	Issue Date: 26/02/2015	Issue No.1
-----------------------	------------------------	------------

**CoverMax Semi-Gloss Enamel**

<b>Product Description</b>	CoverMax Semi-Gloss Enamel offers a premium quality oil based semi-gloss finish suitable for interior and sheltered exteriors. It has been developed for easy brushing and long life protection on all interior surfaces. It wipes clean easily and is resistant to abrasions and hard knocks.						
<b>Areas of Use</b>	Doors, window frames, cupboards and all surfaces where a hard wearing semi-gloss finish is required.						
<b>Australian Standards</b>	AS 2311 The Painting of Buildings						
<b>Special Features</b>	<ul style="list-style-type: none"> <li>* High Opacity</li> <li>* Outstanding flow and levelling</li> </ul>						
<b>Components</b>	<table> <tr> <td>Pigment</td> <td>– Durable, Non Lead</td> </tr> <tr> <td>Binder</td> <td>– Alkyd resin</td> </tr> <tr> <td>Solvent</td> <td>– Mineral Turps</td> </tr> </table>	Pigment	– Durable, Non Lead	Binder	– Alkyd resin	Solvent	– Mineral Turps
Pigment	– Durable, Non Lead						
Binder	– Alkyd resin						
Solvent	– Mineral Turps						
<b>Toxicity</b>	Dry paint is non-toxic but it is flammable. Conforms to AS1647, Part 3.						
<b>Flammability</b>	Product is flammable						
<b>Volume Solids</b>	51%						
<b>Thinning</b>	Mineral Turps – during hot dry conditions it may be necessary to thin with up to 50mL solvent per Litre.						
<b>Method of Application</b>	<p>Brush, roller or spray</p> <p>Stir well before use using a broad flat paddle in a scooping motion.</p> <p>Do not apply if temperature is below 10<sup>0</sup>C or likely to fall below 10<sup>0</sup>C during drying.</p> <p>Do not apply if rain is expected or in hot dry conditions.</p> <p><u>Spray</u> Satisfactory with most equipment. Observe the State Spray Painting Regulations</p>						
<b>Drying</b> (25 <sup>0</sup> C & 50% RH)	<table> <tr> <td>Dry to touch</td> <td>– 4 – 6 hours</td> </tr> <tr> <td>Recoat</td> <td>– 16 Hours</td> </tr> </table> <p>In damp, cool or humid conditions, drying may be extended.</p>	Dry to touch	– 4 – 6 hours	Recoat	– 16 Hours		
Dry to touch	– 4 – 6 hours						
Recoat	– 16 Hours						
<b>Coverage</b>	<p>Approximately 14-16 sq. metres per litre.</p> <p>Coverage will vary depending on the profile and surface porosity.</p> <table> <tr> <td>Dry Film Thickness</td> <td>– 32 microns</td> </tr> <tr> <td>Wet Film Thickness</td> <td>– 63 microns</td> </tr> </table>	Dry Film Thickness	– 32 microns	Wet Film Thickness	– 63 microns		
Dry Film Thickness	– 32 microns						
Wet Film Thickness	– 63 microns						
<b>Clean Up</b>	Mineral Turpentine						

<b>Colour</b>	White
<b>Surface Preparation</b>	<p>Remove all soft, powdered, blistered, loose or flaking paint. Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation. Wash with clean water and allow for drying. Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.</p> <p>Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. If previous paint comes off it must be all removed.</p>
	<p><b><u>Timber New</u></b></p> <p>Sand to remove all graying timber. Fill imperfection with appropriate filler and sand all dressed timber. Dust down and apply one coat of Wood Primer when dry, apply one coat of CoverMax Oil Based Undercoat then apply two tops coats of CoverMax Semi-Gloss Enamel, sanding lightly between coats.</p>
	<p><b><u>MDF New</u></b></p> <p>Sand lightly, dust down and apply one coat of CoverMax Oil Based Undercoat, when dry apply two coats of CoverMax Semi-Gloss Enamel, sand lightly between coats.</p>
	<p><b><u>Brick, Masonry, Fibre Cement New</u></b></p> <p>Ensure surface to be painted is free from mould, dirt, dust or any other contaminant. Fill imperfection with appropriate filler, sand down, dust off, and apply one coat of Binder Sealer. When dry apply two coats of CoverMax Semi-Gloss Enamel, sanding lightly between coats.</p> <p><b><u>Note:</u></b> Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.</p>
<b>Health and Safety</b>	<ul style="list-style-type: none"><li>- Keep out of reach of children</li><li>- Product is highly flammable</li><li>- Wear dust mask if sanding down</li><li>- Wear protective clothing.</li><li>- Ensure good ventilation</li><li>- Do not breathe vapour or spray</li><li>- Wear eye protection</li><li>- Store in a cool place</li></ul>
<b>First Aid</b>	<ul style="list-style-type: none"><li>- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.</li><li>- If Swallowed- drink large amounts of water and seek medical attention.</li></ul>
<b>Environment</b>	<p>Do not tip unused paint or washings down drains</p> <p>Dispose of waste using authorised collection procedures.</p>

<b>Product Code:</b> 959-100	<b>Issue Date:</b> 26/02/2015	<b>Issue No.1</b>
------------------------------	-------------------------------	-------------------

**CoverMax Oil Based Undercoat**

<b>Product Description</b>	CoverMax Oil Based Undercoat is a high quality multi-purpose oil based undercoat suitable for interior and exterior surfaces. It is designed to have high opacity with excellent filling and gloss hold-out properties and outstanding adhesion.						
<b>Areas of Use</b>	Interior and Exterior surfaces.						
<b>Australian Standards</b>	AS 2311 The Painting of Buildings						
<b>Special Features</b>	<ul style="list-style-type: none"> <li>* High Opacity</li> <li>* Outstanding adhesion to a variety of substrates</li> <li>* Excellent gloss hold-out properties</li> </ul>						
<b>Components</b>	<table> <tr> <td>Pigment</td> <td>– Durable, Non Lead</td> </tr> <tr> <td>Binder</td> <td>– Modified alkyd resin</td> </tr> <tr> <td>Solvent</td> <td>– Mineral Turps</td> </tr> </table>	Pigment	– Durable, Non Lead	Binder	– Modified alkyd resin	Solvent	– Mineral Turps
Pigment	– Durable, Non Lead						
Binder	– Modified alkyd resin						
Solvent	– Mineral Turps						
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.						
<b>Flammability</b>	This product is flammable						
<b>Volume Solids</b>	59%						
<b>Thinning</b>	Mineral Turps – during hot dry conditions it may be necessary to thin with up to 50mL solvent per Litre.						
<b>Method of Application</b>	<p>Brush, roller or spray            Stir well before use using a broad flat paddle in a scooping motion.</p> <p>Do not apply if temperature is below 10<sup>0</sup>C or likely to fall below 10<sup>0</sup>C during drying.            Do not apply if rain is expected or in hot dry conditions.</p> <p><u>Spray</u> Satisfactory with most equipment. Observe the State Spray Painting Regulations</p>						
<b>Drying</b> (25 <sup>0</sup> C & 50% RH)	<table> <tr> <td>Dry to touch</td> <td>– 6 – 8 Hours</td> </tr> <tr> <td>Recoat</td> <td>– 16 Hours</td> </tr> </table> <p>In damp, cool or humid conditions, drying may be extended.</p>	Dry to touch	– 6 – 8 Hours	Recoat	– 16 Hours		
Dry to touch	– 6 – 8 Hours						
Recoat	– 16 Hours						
<b>Coverage</b>	<p>Approximately 14-16 sq. metres per litre.            Coverage will vary depending on the profile and porosity of the surface.</p> <table> <tr> <td>Dry Film Thickness</td> <td>– 30 microns</td> </tr> <tr> <td>Wet Film Thickness</td> <td>– 51 microns</td> </tr> </table>	Dry Film Thickness	– 30 microns	Wet Film Thickness	– 51 microns		
Dry Film Thickness	– 30 microns						
Wet Film Thickness	– 51 microns						
<b>Clean Up</b>	Mineral Turps						
<b>Colour</b>	White						

**Surface Preparation**

Remove all soft, powdered, blistered, loose or flaking paint. Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation. Wash with clean water and allow for drying. Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.

Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. If the previous paint comes off it must be all removed.

**Timber New**

Sand to remove all graying timber. Fill imperfections with appropriate filler and sand all dressed timber. Dust down and apply one coat of oil based Wood Primer, when dry apply one coat of CoverMax Oil Based Undercoat then apply two finishing coats, sanding lightly between coats.

**MDF New**

Sand lightly, dust down and apply one coat of CoverMax Oil Based Undercoat, when dry apply two finishing coats, sand lightly between coats.

**Galvanised Steel, Zincalume®, Aluminium**

- New Zincalume®, Galvanised Iron and Aluminium may be left to weather prior to painting. If it is to be painted immediately then surface should be cleaned down using Mineral Turps and non-metallic scourers.
- Surface should be primed with appropriate Metal Primer.
- Apply one coat of CoverMax Oil Based Undercoat followed by finish coats.

**Unpainted Brick, Masonry, Cement Render and Fibre Cement**

- Ensure surface to be painted is free from all contaminants, including mould, moss, lichen, efflorescence etc.
- It is best to use Binder Sealer for these surfaces including Set Plaster and Plaster glass. CoverMax Oil Based Undercoat may be used over Binder Sealer to provide film build if needed.

**Note:** Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.

**Health and Safety**

- Keep out of reach of children
- Product is highly flammable
- Wear dust mask if sanding down
- Wear protective clothing.
- Ensure good ventilation
- Do not breathe vapour or spray
- Wear eye protection
- Store in a cool place

**First Aid**

- Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
- If Swallowed- drink large amounts of water and seek medical attention.

**Environment**

Do not tip unused paint or washings down drains  
Dispose of waste using authorised collection procedures.

Product Code: 961-100

Issue Date: 26/02/2015

Issue No.1

**CoverMax Quick Dry Oil Based Undercoat**

<b>Product Description</b>	CoverMax Quick Dry Oil Based Undercoat is a multi-purpose quick dry oil based primer sealer applicable for all types of interior and exterior surfaces. It is designed to have high opacity, outstanding adhesion and excellent stain blocking ability, ideal for water stains, nicotine, ink, graffiti, crayon markers, rust and smoke stains.						
<b>Areas of Use</b>	Interior and Exterior surfaces.						
<b>Australian Standard References</b>	AS 2311 The Painting of Buildings APAS 0016/1 APAS 0181						
<b>Special Features</b>	<ul style="list-style-type: none"> <li>* Excellent Stain Blocking</li> <li>* High Opacity</li> <li>* Outstanding adhesion to a variety of substrates</li> <li>* May be over-coated without sanding</li> </ul>						
<b>Components</b>	<table border="0" style="width: 100%;"> <tr> <td style="width: 150px;">Pigment</td> <td>– Durable, Non Lead</td> </tr> <tr> <td>Binder</td> <td>– Modified alkyd resin</td> </tr> <tr> <td>Solvent</td> <td>– Mineral Turps</td> </tr> </table>	Pigment	– Durable, Non Lead	Binder	– Modified alkyd resin	Solvent	– Mineral Turps
Pigment	– Durable, Non Lead						
Binder	– Modified alkyd resin						
Solvent	– Mineral Turps						
<b>Toxicity</b>	Dry paint is non toxic. Conforms to AS1647, Part 3.						
<b>Volume Solids</b>	50%						
<b>Thinning</b>	Mineral Turps – during hot dry conditions it may be necessary to thin with up to 50mL solvent per Litre.						
<b>Method of Application</b>	<p>Brush, roller or spray</p> <p>Stir well before use using a broad flat paddle in a scooping motion.</p> <p>Do not apply if temperature is below 10<sup>0</sup>C or likely to fall below 10<sup>0</sup>C during drying.</p> <p>Do not apply if rain is expected or in hot dry conditions.</p> <p><u>Spray</u> Satisfactory with most equipment. Observe the State Spray Painting Regulations</p>						
<b>Drying</b> (25 <sup>0</sup> C & 50% RH)	<table border="0" style="width: 100%;"> <tr> <td style="width: 150px;">Dry to touch</td> <td>– 30 Minutes</td> </tr> <tr> <td>Recoat</td> <td>– 1 Hour</td> </tr> </table> <p>In damp, cool or humid conditions, drying may be extended.</p>	Dry to touch	– 30 Minutes	Recoat	– 1 Hour		
Dry to touch	– 30 Minutes						
Recoat	– 1 Hour						
<b>Coverage</b>	<p>Approximately 10-12 sq. metres per litre.</p> <p>Coverage will vary depending on the profile and porosity of the surface.</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 150px;">Dry Film Thickness</td> <td>– 25 microns</td> </tr> <tr> <td>Wet Film Thickness</td> <td>– 50 microns</td> </tr> </table>	Dry Film Thickness	– 25 microns	Wet Film Thickness	– 50 microns		
Dry Film Thickness	– 25 microns						
Wet Film Thickness	– 50 microns						



<b>Clean Up</b>	Mineral Turps
<b>Colour</b>	White
<b>Surface Preparation</b>	<p>Remove all soft, powdered, blistered, loose or flaking paint. Remove all traces of grease, dirt, oil or smoke stain using a suitable preparation. Wash with clean water and allow for drying. Repair any cracks or surface defects with an appropriate filler. Sand smooth and dust off.</p> <p>Previously painted surfaces must be sound and have good adhesion. This can be checked by cutting an "X" with a sharp blade, press a piece of clear tape over the "X" as firmly as possible with the ball of the thumb then as quickly as possible, tear off the tape in one movement. If the previous paint comes off it must be removed before repainting.</p> <p>If stain is due to leaks or damage to substrate underneath the coating it must be repaired prior to painting to achieve effective rectification of the problem.</p> <p><b>Note:</b> Mould, fungal infected surfaces and efflorescence must be treated to eliminate the possibility of recurrence.</p>
<b>Health and Safety</b>	<ul style="list-style-type: none"> <li>– Keep out of reach of children</li> <li>– Product is highly flammable</li> <li>– Wear dust mask if sanding down</li> <li>– Wear protective clothing.</li> <li>– Ensure good ventilation</li> <li>– Do not breathe vapour or spray</li> <li>– Wear eye protection</li> <li>– Store in a cool place</li> </ul>
<b>First Aid</b>	<ul style="list-style-type: none"> <li>– Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.</li> <li>– If Swallowed- drink large amounts of water and seek medical attention.</li> </ul>
<b>Environment</b>	<p>Do not tip unused paint or washings down drains</p> <p>Dispose of waste using authorised collection procedures.</p>